

# CCS-580D Digital Delegate Discussion Unit



- Digital audio for good sound quality.
- Built-in loudspeaker and pluggable microphone.
- Good ability for resistance to Mobile interference.
- Reduce sound impact and wind shield.
- Metal microphone shell bottom.
- Light ring indicator on microphone stem, lights up red when microphone is on.

**CCS-580 Series** is a new Digital Conference System, This series includes Controller Unit with Digital Anti Feedback (CCS-580M), Discussion Desktop Unit for Chairman (CCS-580C) and Discussion Desktop Unit for Delegate (CCS-580D).

**CCS-580 Series** supports multiple meeting for :

- Corporate meeting Rooms.
- Government meeting room & City Council Meeting.
- Education institutions.
- Courtrooms.
- Non-profit organizations.

## Feature

- Digital audio for good sound quality.
- Built-in hi-fi loudspeaker and pluggable microphone.
- Removeable gooseneck microphone with light ring indicator on microphone stem, light up red when microphone turn on.
- High sensitivity microphone.
- Good ability for resistance to Mobile interference.
- Speaking button and indicator lamp that can show and control the state of speech.
- Two groups of 3.5mm stereo sound output socket; can be used as speech sound input and earphone connection.
- Rotary volume control for adjusting built-in loudspeaker or headphone volume (when headphone connect).
- Daisy-Chain connection.
- Connecting cable 2.3m, 8P core line, convenient installation can increase efficiency.
- The power for units is supplied by the master controller.
- Reduce sound impact and wind shield.
- Metal microphone shell bottom.

## Certifications : CE and RoHS

The CCS-580C conforms to standard

- IEC 62321
- EN 55013 , EN 55020 , EN 61000

## Specifications

|                       |                       |
|-----------------------|-----------------------|
| Power Supply          | DC 9V by Control unit |
| Power Consumption     | 80mA                  |
| Interface Type        | 8P-DIN                |
| Earphone Output       | 3.5mm stereo jack     |
| Installation          | Desktop               |
| Input Impedance       | 1 K $\Omega$          |
| Connection Mode       | Daisy-Chain           |
| Crosstalk Attenuation | >60 dB                |
| Speaker Power         | 2W                    |
| Microphone Type       | Condenser             |
| Polar pattern         | Ultra Cardioid        |
| Frequency response    | 50Hz-17kHz            |
| Signal-to-Noise Ratio | 68dB(A-Wieght)        |
| Sensitivity           | -43 dBV/Pa            |
| Length of Microphone  | 500mm                 |
| Color                 | Iron gray             |
| Dimensions            | W163xH60xD125 mm      |
| Weight                | 800g                  |

# CCS-580D Digital Delegate Discussion Unit

## Diagram

